

	B		A							
4										
					3					
S EXA	XAMPLE									
any non-conformity or damage										
er of t	which does not comply with or of the Parties or by a third party Idation, technical notice.)									
		-								
Intry R	Jurisd	liction & Cont Not Listed	trol List		2					
3W	W53AB									
				J						
		CUSTON		MOD N°						
	CUSTOMER DRAWING									
	Receptacl				-					
ar		NPRDS / PROJECT <b>859</b>								
This document is the property of SOURIAU										
I.CC	JIVI	it must not be reproduced or communicated without permission								
	DRG N°			SHEET	-					
W5	SAB-C			1/2	J					
	В		А							

	т	۵	т	п	D	0	
		Contact Layout				Panel cutout	
4		4         4         4         4         4           6         10         1         0         6				JAM NUT RECEPTACLE (TYPE 7)	M
	Contact position         Loca           ID         (mm)           A         +112 (2.84)           B         +225 (5.72)           C         +336 (8.53)           D         +450 (11.43)           E         +.450 (11.43)           G         +336 (8.57)           H         +225 (5.72)           J         -225 (5.72)           J         -336 (8.53)           K         -336 (8.53)	Contacts (Insert arrangement 22-53)           ation         Contact position ID         Location (mm)         Y-axis         Y-axis (mm)         Y-axis           +455 (11.56)         g         -225 (5.72)         -260 (6.60)         -235 (6.53)        195 (4.96)           +330 (9.91)         f         -336 (8.53)        095 (1.65)         +.006 (1.65)         +.006 (1.65)           +130 (3.30)         h         -336 (8.53)         +.095 (1.65)        330 (8.53)         +.095 (1.65)           +300 (0.00)         k        336 (8.53)         +.095 (1.65)        330 (8.53)         +.095 (1.65)           -130 (3.30)         m        225 (5.72)         +.200 (5.60)        325 (8.26)         n        112 (2.84)         +.325 (8.26)           -410 (10.41)         g         +.112 (2.84)         +.195 (4.95)        325 (8.26) (7.2)         +.195 (4.95)           -325 (8.26)         g         +.112 (2.84)         +.195 (4.95)        325 (8.26) (7.2)         +.103 (3.30 (3.0)				ØC	
ω	L450 (11.43) M450 (11.43) P336 (8.53) R225 (5.72) S112 (2.84) T +.000 (0.00) U +.112 (2.84) V +.225 (5.72) Contact Loca	-130 (3.30)         s         +225 (5.72)         +.000 (0.00)           +000 (0.00)         1         +225 (5.72)        130 (3.30)           +130 (3.30)         u         +.112 (2.84)        195 (4.95)           +325 (8.26)         v         +.000 (0.00)        260 (6.60)           +330 (9.91)         w        112 (2.84)        195 (4.95)           +455 (11.56)         x        225 (5.72)        130 (3.30)           +390 (9.91)         y        225 (5.72)         +.130 (3.0)           +396 (9.91)         y        225 (5.72)         +.130 (3.0)           +396 (9.91)         y        225 (5.72)         +.130 (3.0)           +396 (9.91)         y        225 (5.72)         +.130 (3.0)           +326 (2.66)         Z        225 (5.72)         +.130 (3.0)           +226 (6.60)         AA        112 (2.84)         +.195 (4.95)           Contact         Contact         Location         V.avie				Dim         Nomin           B         40.26+0/           ØC         41.53+0.2	-0.25
	size no. co	reads         position ID         reads         reads           (mm)         (mm)         (mm)         (mm)         (mm)           +195 (4.95)         BB         +000 (0.00)         +130 (3.30)           +065 (1.65)         DD         +112 (2.84)         +065 (1.65)           -065 (1.65)         DD         +112 (2.84)         -065 (1.65)           -260 (6.00)         FF         -112 (2.84)         -065 (1.65)           -220 (6.00)         FF         -112 (2.84)         -065 (1.65)           -326 (9.20)         FG         -112 (2.84)         -065 (1.65)           -326 (9.26)              imber of         Size         Service         Contact         Supersedes           ontacts         contacts         rating         location         Supersedes           53         20         I         Ail         MS20056-53 <td></td> <td></td> <td></td> <td>SOURIAU shall not be li due to a use of the F the Specifications issued</td> <td>roducts which</td>				SOURIAU shall not be li due to a use of the F the Specifications issued	roducts which
N						(professional rec	
					ISS D Designed By:	0-2016 First Release ATE Latest modification - by Date:	
-					SCALE NA	Gen Tol	eral linear erances: ±
					FORMAT A3	SO 8D	RIAU.CO JRIAU 723W5
	Н	G	F I	E	D	C	

