| | т <u></u> | m | | 0 | E D D D D D D D D D D D D D D D D D D D | A | | _ | |
|--|--|---|-------------|--|--|------------------------------------|--------|------------------|--|
| CHARACTERISTICS Standard : Based on MIL-DTL-38999 Series II Shell Material : :::::::::::::::::::::::::::::::::: | | | | | | | | | |
| CHARACTERISTICS Standard : Based on MII-DTL-38999 Series II Shell Material : Standard : Rased on MII-DTL-38999 Series II Shell Material : Muminiam Shell Material : Shell | Keving Sh | own as example | | | | | | | |
| Shell Material : Alumnum Shell Material : Alumnum Shell Material : Biok Zinc Kickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Contacts : Copper Alloy -Contacts : Sold over copper Alloy 0.8µm minimum -Durability : Sold over copper Alloy 0.8µm minimum -Mass : 21.28 g + 10% BASIC SERIES: : 8D Sold Contact : Sold in contact Sold Contact TYPE : Sold contact Sold Contact Comper Alloy : Sold contact BASIC SERIES: : 8D 7 11 <td>CHARACTERISTICS</td> <td>Connector dimension Dim Nominal</td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> | CHARACTERISTICS | Connector dimension Dim Nominal | | | | | | | |
| -Seals & Groumet : Silcon Elastomer Country Jurisdiction & Control List 2 -Seals & Groumet : Gold over copper Ally 0.8,µm minimum PN: 8D711Z99BN 2 -Derivered with Souriau contacts and Accessories PN: 8D711Z99BN 2 -Temperature Range :-65°C to +17°C A 01-10-2016 First Release Mod N* -Sait Spray : 500 hours Mass : 21.28 g ± 10% MOD N* | -Shell Plating: Black Zinc Nickel-Insulator: Thermoplastic | B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 | | due to a use of the the Specifications issue | e Products which does not cor d by either of the Parties or b | mply with y a third party | | | |
| -Delivered with Souriau contacts and Accessories -Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 21.28 g ± 10% BASIC SERIES: 8D 7 _ 11 Z 99 B N BASIC SERIES: 8D 7 _ 11 Z 99 B N CONTACT TYPE : Standard Crimp Contact SHELL TYPE : Jam nut Receptacle CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 11 PLATING : Z = Black Zinc Nickel CONTACT TYPE : Source Zince Zi | | | | | - | |] | 2 | |
| - Salt Spray : 500 hours -Mass : 21.28 g ± 10% - Mass : 21.28 g ± 10% - Mas | | | | PN: | 8D711Z99BN | | | | |
| -Mass : 21.28 g ± 10% ISS DATE Latest modification - by Date: CUSTOMER DRAWING Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series: SHELL TYPE: CONTACT TYPE: Stell Size: 11 2 0 NPRDS NPRDS NPRDS NPRDS SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SCALE NA SOURIAU WWW.SOURIAU.COM It must not be reproduced or communicated without permission communicated with | | | A 01-10-201 | .6 First Release | | | | | |
| BASIC SERIES: 8D 7 - 11 Z 99 B N SALC NRDS / PROJECT 859 1 SHELL TYPE : Jam nut Receptacle ORIENTATION : N SHELL SIZE : 11 NA Image: Contact type : Standard Crimp Contact This document is the property of SOURIAU SOURIAU This document is the property of SOURIAU PLATING : Z = Black Zinc Nickel CONTACT TYPE : SOCKET(500 Matings) CONTACT LAYOUT : 11-99 Image: Contact Layout : 11-99 Ima | | | | | y | CUSTOMER DRAWING | MOD N° | | |
| BASIC SERIES. SUP / L II Z 99 B N III IIII IIIII IIII IIII IIII IIII IIII IIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIIII | | | TITLE | A | luminium Receptacl | e 8D series | | | |
| CONTACT TYPE : Standard Crimp Contact ORIENTATION : N SHELL SIZE : 11 CONTACT TYPE : SOCKET(500 Matings) PLATING : Z = Black Zinc Nickel CONTACT LAYOUT : 11-99 FORMAT SOURIAU ORIENTATION : N | | N | | | Tolerances: | | | | |
| PLATING : Z = Black Zinc Nickel FORMAT SOURIAU DRG N° SHEET | CONTACT TYPE : Standard Crimp Contact | | SOURIAL | J WWW.SO | URIAU.COM | SOURIAU it must not be reproduc | ced or | | |
| | | | | | | communicated without pe | SHEET | $\left \right $ | |
| H G F E D C B A | H G F | E | | | BD711Z99BN-C | A | 1/2 | | |

| ſ | Т | ۵ | г | п | D | C | σ | ⊳ | |
|---|---|---|---|---|-----------------------------------|--|---|--|------|
| 4 | -X | Contact Layout $f \qquad A \qquad F \qquad A \qquad A$ | | | | Panel cutout JAM NUT RECEPTACLE (TYPE 7) | Ā | | 4 |
| | Conta positi ID A B C D E F F G Shell Arrangement Numb | X-axis (mm) Y-axis (mm) +.065 (1.65) +.113 (2.87) +.130 (3.30) +.000 (0.00) +.065 (1.65) 113 (2.87) 015 (1.65) 113 (2.87) 130 (3.30) +.000 (0.00) 065 (1.65) +.113 (2.87) 005 (1.65) +.113 (2.87) +.000 (0.00) +.000 (0.00) | 1 | | | ØC | | | |
| ω | size no. cont 11 -99 7 | acts contacts rating location | | | | Dim Nominal B 19.59+0/-0. ØC 20.96+0.25. | .25 | | 3 |
| | _ | | | | | due to a use of the Pro the Specifications issued by | ble for any non-conformity or da oducts which does not comply w r either of the Parties or by a thi mmendation, technical notice.) | rith rd party | |
| 2 | | | | | A 01-10-2016 | PN: 8C | | & Control List .isted | 2 |
| | | | | | ISS DATE Designed By: TITLE | Latest modification - by Date: | cus ninium Receptacle 8D | MOD N° TOMER DRAWING Series | |
| - | | | | | SCALE NA SOURIAU | | ances: IAU.COM | PRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or communicated without permission | _ 1 |
| | | | | | FORMAT A3 | | RIAU DRG N° 711Z99BN-C | SHEET 2/2 | |
| Ľ | Н | G | F | E | D | С | В | A | _ |