

# Housing - HC-B 10-KML-H-M1PG16 - 1460286

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

HEAVYCON B10 coupling housing, with single locking latch, height: 77.5 mm, with 1 x Pg16 screw connection, straight cable outlet



## **Key Commercial Data**

Packing unit	10 STK
GTIN	4 046356 794602
GTIN	4046356794602

### Technical data

#### **Dimensions**

Height	77.5 mm
Width	43 mm
Length	73 mm
Wrench size, union nut	22 mm
External cable diameter	7.5 mm 15 mm

### Ambient conditions

Degree of protection of housing (IP)	IP65
Ambient temperature (operation)	-40 °C 125 °C

### General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
Size	B10
Housing type	Coupling housings
Locking type	with single locking latch
No. of cable outlets	1
Cable outlet	straight
Screw connection	with
Type of the screw connection	1x Pg16
Housing material	Aluminum die-cast
Housing surface material	Powder-coated, gray
Seal material	NBR
Material lock	Stainless steel, handle: PA
Material grip body interlock	PA

08/18/2018 Page 1 / 2



# Housing - HC-B 10-KML-H-M1PG16 - 1460286


## Technical data

### **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## **Drawings**

#### Dimensional drawing



Dimensional drawing

## Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC

RU C-DE.Al30.B.01102

Phoenix Contact 2018 @ - all rights reserved <code>http://www.phoenixcontact.com</code>

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstr. 8 32825 Blomberg Germany

Tel. +49 5235 300 Fax +49 5235 3 41200

http://www.phoenixcontact.com