	D I		
4	Z Thread Reference of the second se	ØF F F F F F F F F F F F F F	
ယ			LAYOUT SHOWN AS EXAMPLE
		Keying Shown as example	
N	CHARACTERISTICS-Standard : Based on MIL-DTL-38999 Series III-Shell Material: Aluminium-Shell Plating: Olive drab Cadmium-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer-Contact Plating: Gold over copper Alloy 0.8µm minimum-Durability: 500 Mating cycles	Connector dimensionDimNominalF19.05 MaxZ31.5 MaxVV THREADM15x1-6g	SOURIAU shall not be liable for any non-conformity or damage
	-Delivered with Souriau contacts and Accessories		PN: 8D111W99BN
	-Temperature Range <u>:</u> -65°C to +175°C -Salt Spray : 500 hours		A 27-09-2016 First Release ISS DATE Latest modification - by MOD N°
			Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Inline plug 8D series
	BASIC SERIES: 8D 1 - 11 W SHELL TYPE : In line Receptacle - 11 W CONTACT TYPE : Standard Crimp Contact - 5 SHELL SIZE : 11 - 0 - 0	CONTACT TYPE : SOCKET(
	PLATING : W = Olive drab Cadmium		A3 8D111W99BN-C 1/2
	H G I	F E	D C B A

ſ	Т	۵	н т	ш		0	Β	A		
4	-X Contr positi ID A B C	Actuals Franks (mm) (mm) +.065 (1.65) +.113 (2.87) +.130 (3.30) +.000 (0.00)								4
ω	Shell Arrangement Numb size no. cont 11 -99 7	065 (1.65) 113 (2.87) 130 (3.30) +.000 (0.00) 065 (1.65) +.113 (2.87) +.000 (0.00) +.000 (0.00) +.000 (0.00) +.000 (0.00) ver of Size Service Contact contacts rating location								3
	_	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)								
N						PN: 8D		2		
					ISS DATE Designed By:	5 First Release Latest modification - by Date:		OMER DRAWING	MOD N°	
_					SCALE NA	Genera Tolera ±	ances: T	SETIES PRDS / PROJECT 859 his document is the proper SOURIAU	rty of	1
					FORMAT A3	SOU 8D1	م RIAU DRG N° 11W99BN-C	it must not be reproduced mmunicated without perm		
	Н	G	I F I	E	/ D	C	В	A		