l	т <u>Ω</u> т	m		0	₿ >		
4	Z						
с у	Keying Show	n as example		LAYOUT SHOWN AS EXA	MPLE		
	CHARACTERISTICS	Connector dimension					
	-Standard : Based on MIL-DTL-38999 Series III	Dim Nominal					
2	Shell Material: AluminiumØS29.4 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
	Contact Plating : Gold over copper Alloy 0.8µm minimum Durability : 500 Mating cycles Delivered with Souriau contacts and Accessories PN: 8D513W08SA						
ſ	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours		A 19-10-2016	First Release			
	-Salt Spray : 500 hours -Mass : 26.6 g ± 10%		ISS DATE	Latest modification - by		MOD N°	
			Designed By: TITLE	Date: CUSTOMER DRAWING Aluminium Plug 8D series			
1	BASIC SERIES: 8D 5 - 13 W 08 S A SHELL TYPE : Plug with RFI Shielding - 13 W 08 S A		SCALE -	General linear Tolerances:	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 CONTACT TYPE : SOCKET(500 Matings)			SOURIAU WWW.SOURIAU.COM This document is the prop SOURIAU it must not be reproduce communicated without per			
	PLATING : W = Olive drab Cadmium	CONTACT LAYOUT : 13-08	•	SOURIAU I		SHEET	
		1	A3	8D513W0		1/2	
		Ε	D	C			

	Ŧ	۵	וד-	m	D	0			
		Contact Layout							
4	د	$ \begin{array}{c} & & & \\ & & & \\ & & & \\ & & $							
	0051 11 2 4 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	(mm) (mm) 8 +.165 (1.65) +.157 (3.99) 8 +.170 (4.32) +.000 (0.00) C +.120 (3.05) 120 (3.05) D 000 (0.00) 170 (4.32) E 120 (3.05) 120 (3.05) F 170 (4.32) +.000 (0.00)							
ω	size no. co	mber of Size Service Contact Superseder ontacts contacts rating location 8 20 I All MS20051-6							
	-					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either o (professional recommendat			
м						PN: 8D513V			
					A 19-10-20 ISS DATE Designed By:	016 First Release			
					SCALE	General linear Tolerances:			
					SOURIA				
					FORMAT A3	SOURIAU 8D513W			
l	Н	G	F	E	D	C C			

