APPLIC <i>A</i>			DARD										
		PERATING EMPERATUR	E RANGE	-35°C TO +85°C(NO	-35°C TO +85°C (NOTES 1) TEM		RAGE PERATURE RANGE		E	-10°C TO +60°C			
RATING	V	OLTAGE		30V AC			APPLICABLE CONNECTOR			BM10*(0.6)-*DP-0.4		4V (**)	
	С	URRENT		0. 3A									
				SPEC	IFIC <i>A</i>	OIT/	NS						
	TEN		TEST METHOD				REQUIREMENTS				QT	АТ	
CONST			I				14000	DINO TO		A)4//11/0	1		
GENERAL EXAMINATION			CONFIRMED VISUALLY AND BY MEASURING INSTRUMENT.				ACCO	RDING TO	אט כ	AWING.	X	X	
MARKING			CONFIRMED VISUALLY.								Х	Х	
ELECTR													
CONTACT RESISTANCE			20mV AC OR LESS 1khz,1m A .				100mΩ MAX.				X	_	
INSULATION RESISTANCE			100V DC.				50MΩ MIN.				Х	-	
VOLTAGE F	PRC	OF	100V AC FOR 1 min.				NO FLASHOVER OR BREAKDOWN.				X	1_	
MECHA	NIC	CAL CHA	RACT	ERISTICS			1						
MECHANICAL OPERATION			10TIMES INSERTIONS AND EXTRACTIONS.				(Î) CONTACT RESISTANCE: 100mΩ MAX. (② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.				X	_	
VIBRATION			FREQUENCY 10 TO 55 TO 10 Hz,APPROX 5min, SINGLE AMPLITUDE 0.75 mm,10CYCLES, FOR 3 DIRECTIONS.				 NO ELECTRICAL DISCONTINUITY OF 1 μs. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				. X	-	
SHOCK			490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.				 NO ELECTRICAL DISCONTINUITY OF 1 μs. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				. X	-	
ENVIRO	N	/IENTAL	CHARA	ACTERISTICS								'	
RAPID CHANGE OF TEMPERATURE			TEMPERATURE -55 → +85 °C TIME 30 → 30 min UNDER 5 CYCLES. (RELOCATION TIME TO CHAMBER: WITHIN 2 ~3 MIN)				 CONTACT RESISTANCE: 100mΩ MAX. INSULATION RESISTANCE: 50MΩ MIN. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				1 V	-	
DAMP HEAT (STEADY STATE)			EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.								~ I v	-	
SULPHUR DIIOXIDE			EXPOSED IN 25 PPM FOR 96h,25°C,75%. (REFER TO JIS C 60068)			 CONTACT RESISTANCE: 100mΩ MAX. NO DAMAGE, CRACK OR LOOSENESS OF PARTS. 				(. X	-		
COU	NT	DE	SCRIPTION	ON OF REVISIONS		DESI	GNED			CHECKED D		ATE	
								\Box					
REMARKS NOTE1: INCL	LUD	E THE TEMPI	ERATURE RISING BY CURRENT ed, refer to JIS C 5402 and IEC 60512					APPROVED CHECKED		KH. IKEDA KY. MIDORIKAWA	+	08.08	
l Inless oth	ner.	vise specifi				DESIGNED			YH. MICHIDA	09. 08. 08			
		•	•				DRAWN RAWING NO.		'IN	YH. MICHIDA 09. 08. 08 ELC4-318409-75			
ЖS				CATION SHEET		PART NO.			BM10NB (0. 6) -*DS-0. 4V (75)				
11/2				ELECTRIC CO., LTD.		CODE NO.				CL684	Δ	1/1	